Replacement Shaker Screens




	Rej
LAB TESTED FIELD PROVEN	
DEPENDABLE DELIVERY	
VITAL STATISTICS	
Screen Style	
Frame Support,	
Metal Backed	
Overall Width	
24.00"	
Overall Length	
46.25"	
API Non-Blanked Area	_
5.36 ft ²	
Weight	
30 lbs	
Materials of Construction	
Mesh	
304 SS	
Backing	
A500 grade carbon steel	
Frame	
A500 grade carbon steel	
Seal	
NBR Flat Seal	TI
Availablity in Sierra [™] style	FI
YES	
SHIPPING	
Screens per box	
1	
Box Dimensions	
29" x 50" x 2"	
Box Weight	
34 lbs	



STROX SYSTEMS, LLC Office: +1.713.589.9900 Email: sales@stroxsystems.com www.stroxsystems.com

Replacement for



API Performance Characteristics

API #	Cut Point D ₁₀₀ , μ	Conductance kD/mm	API #	Cut Point D ₁₀₀ , μ	Conductance kD/mm
20	794.6	11.00	120	120.1	1.48
30	646.3	12.76	140	99.2	1.01
35	539.5	8.36	170	85.6	0.76
45	381.5	7.49	200	73.3	0.62
50	293.7	4.84	230	68.6	0.57
60	260.3	2.69	270	53.8	0.39
70	207.8	2.06	325	48.8	0.38
80	176.1	1.77	400	36.0	0.25
100	142.5	2.06			

These Specifications conform to API RP 13C "Recommended Practice on Drilling Fluid Processing Systems Evaluation", latest edition

ALSO available:

- MARKET GRADE common wire cloth mesh—on request
- BLANK Screen with sheet steel replacing wire cloth
- SCREEN HOLE PLUGS for damaged mesh
- SIERRAN corrugated surface for increased flow performance



HOUSTON TEXAS Admin / Sales / Shipping

8524 Hwy 6 North #438

Houston, TX 77095

MIDLAND TEXAS Warehouse / Shipping

1110 South FM 1788 #85 Midland, TX 79706 LOUISIANA Production / Shipping

618 Hangar Drive New Iberia, LA 70560

Orbital [®] is a registered trademark of Vortex Fluid Systems Inc.

Copyright ©2021 Strox Systems, LLC. All product and company names are trademarks[™] or registered trademarks[®] of their respective holders. *Strox[™]*, *Screen Logix[™]* and *Sierra[™]* are Trademarks of Strox Systems, LLC. All specifications are subject to change without notice.